



PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/05/2019

Revision date: 03/05/2019

Supersedes: 06/12/2018

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE
Product code : 449001

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coating.
Recommended use : Coatings and paints

1.3. Supplier

Rodda Paint Co.
6107 North Marine Drive
Portland, Oregon 97203 - US
T (503) 521-4300
www.rodmapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin sensitization, Category H317 : May cause an allergic skin reaction

1
Carcinogenicity Category 2 H351 : Suspected of causing cancer

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H317 - May cause an allergic skin reaction
H351 - Suspected of causing cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust, mist, spray, vapors.
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P302+P352 - If on skin: Wash with plenty of warm, soapy water
P308+P313 - If exposed or concerned: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
TITANIUM DIOXIDE	(CAS-No.) 13463-67-7	16.2	Carc. 2, H351
WATER BASED DISPERSABLE EPOXY RESIN	(CAS-No.) 25068-38-6	0.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, vapors, spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing mist, vapors, spray.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

WATER BASED DISPERSABLE EPOXY RESIN (25068-38-6)

Not applicable

TITANIUM DIOXIDE (13463-67-7)

ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Insufficient ventilation: wear respiratory protection. Protective clothing.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : white
- Odor : mild

PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: No data available
pH	: 8.5 - 9.5
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity	: No data available
Specific gravity / density	: 9.98 lb/gal
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 2000 cSt
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Carbon dioxide. Carbon monoxide. fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

WATER BASED DISPERSABLE EPOXY RESIN (25068-38-6)

LD50 oral rat	11400 mg/kg
ATE US (oral)	11400 mg/kg body weight

TITANIUM DIOXIDE (13463-67-7)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Skin corrosion/irritation : Not classified
pH: 8.5 - 9.5

Serious eye damage/irritation : Not classified
pH: 8.5 - 9.5

PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

TITANIUM DIOXIDE (13463-67-7)	
IARC group	2B - Possibly Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified
Specific target organ toxicity – repeated exposure : Not classified
Aspiration hazard : Not classified
Symptoms/effects after skin contact : May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

WATER BASED DISPERSABLE EPOXY RESIN (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under Chemical Data Reporting Rule (formerly the Inventory Update Reporting Rule), i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 711).

TITANIUM DIOXIDE (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

WATER BASED DISPERSABLE EPOXY RESIN (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

TITANIUM DIOXIDE (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

WATER BASED DISPERSABLE EPOXY RESIN (25068-38-6)

Listed on the EU - No-Longer Polymers List (67/548/EEC)

TITANIUM DIOXIDE (13463-67-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

National regulations

WATER BASED DISPERSABLE EPOXY RESIN (25068-38-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations



WARNING

This product can expose you to TITANIUM DIOXIDE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

TITANIUM DIOXIDE (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

PROTECH PRECAT EPOXY SEMIGLOSS WHITE BASE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TITANIUM DIOXIDE (13463-67-7)

U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 03/05/2019

Full text of H-phrases:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects

Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 0 Minimal Hazard - Materials that will not burn
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection : C
C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.