

Rodda
PAINT

COMMERCIAL • INDUSTRIAL • RESIDENTIAL

Super II

INTERIOR WATERBORNE 100% ACRYLIC
PerformancePlus

The "GO TO" Coating when Product Quality is of the
Essence to ensure Outstanding Application Performance and
Guaranteed Customer Satisfaction!

- "Best in Class" Touch-up
- Outstanding Durability and Washability
- Excellent Flow and Leveling
- Superior Adhesion and Stain Resistance
- Excellent for Walls, Doors, Woodwork and Trim
- High Performance Tested and Rated



The Rodda Paint Difference



The Paint that Does the Thinking for You - Quality Product for Outstanding Application Performance and Guaranteed Customer Satisfaction!

Description:

Super II is formulated with the latest Acrylic Waterborne Technology to deliver High Performance characteristics with Maximum Durability, Premium Stain Resistance and Outstanding Washability.

Excellent Flow and Leveling and Superior Adhesion to porous and non-porous surfaces, make Super II the best choice over oil base paints and previously stained wood surfaces.

Exceptional Durability, Non-yellowing, Fast dry and Low odor make Super II ideal for interior use.

Most paint can be made to look good when applied by professionals, however, all paints are not equal in terms of washability, burnish, stain resistance and color encapsulation when washing walls painted with darker colors. Professional applicators find higher quality products like Super II have less expensive application costs where improved flow and leveling contribute to maximum hide and spread rate coverage.

"Over the years, I've built the good reputation of my business by not taking shortcuts and using quality paint. After a job is completed, my customers expect the walls and trim I've painted to wash well and stand up to everyday bumps and scuffs. That's why I use Super II from Rodda Paint. My name depends on it."

– Painting Contractor, WA State

Recommended Uses:

- Institutional, Commercial and Residential applications
- New Housing Construction with Improved Washability requirement
- Kitchens, Bathrooms
- Woodwork, Doors, Trim
- Masonry Surfaces
- Over Oil-based Paints and Non-porous Surfaces
- New or Previously Stained Wood Surfaces

Features:

- "Best in Class" Touch-up
- Outstanding Durability and Washability
- Excellent Flow and Leveling
- Superior Adhesion and Stain Resistance
- Excellent for Walls, Doors, Woodwork and Trim
- High Performance Tested and Rated
- Higher Volume Solids for Better Hide and Coverage

Super II Technical Data

Sheen	MPI Approved	Gloss Level	Base	VOC	Volume Solids	Film Thickness		Reducers	Minimum Application Temperature	Application and Curing at 77F and 50% Relative Humidity	Application Recommendation
						Wet	Dry				
Eggshell (43 Series)	#138	2	White	< 85 g/L	39% (Varies by Base and Color)	3.8 - 5.1 mils	1.5 - 2.0 mils	Not normally recommended. Reduce sparingly with water for spray applications	50F	• Dry to Touch: 30 mins • Dry to Recoat: 8 hrs	Polyester Brush - 3/8"-3/4" nap Synthetic Roller Cover - 10 psi cap pressure, HVLP Spray with 1.3 tip - 2000 psi Pressure Airless Spray with .015-.019 tip
			Deep								
			Neutral								
Semi Gloss (44 Series)	#141	5	White	34% (Varies by Base and Color)	4.4 - 5.9 mils	1.5 - 2.0 mils					
			Deep								
			Neutral								

For additional details please see your Rodda Representative for the Technical Data Sheet (TDS) for this product.

Made in the Northwest, for the Northwest, since 1932.



6107 N. Marine Drive, Portland, OR
503-521-4300 | 800-452-2315

RoddaPaint.com | Follow Us [f](#) [@](#) [in](#) [v](#)

Ask your Rodda Paint representative about the new Cascadia Color Collection.

