

# Driveline

Acrylic Traffic & Striping Paint White  
57341A



## COMPLIANCE INDICATORS

at

## DESCRIPTION

An exterior pigmented acrylic latex emulsion striping paint

## RECOMMENDED USES

Driveline striping paint is an exceptionally durable and fast drying water based traffic marking paint intended for use in areas where laying cones is unacceptable.

## FEATURES

Meets TT-P-1952  
Lead & Chromate free  
Fast drying

## TECHNICAL CHARACTERISTICS

Bases	VOC(g/L)*
White (57341A)	
Yellow Base (57342A)	73.6 g/L (0.61 lbs/gal)
Red Base (57344A)	73.6 g/L (0.61 lbs/gal)

\*Before thinning and colorants

## FINISH

Gloss: <5

Sheen: <5

## SOLIDS & DENSITY

Volume: 62.6

Weight: 79.5

Density: 14.95

## FILM THICKNESS (PER COAT)

Wet: 3.0 - mils

Dry: 2.0 - mils

## VISCOSITY

80 - 90 KU

## DRYING TIME

at 77°F and 50% Relative Humidity

1 minute



# TECHNICAL DATA SHEET

## SURFACE PREPARATION

**Surface preparation is important.** All surfaces must be cured, clean, dry, free of mildew, or other contaminants before coating. Ideal surface temperatures for coating are 50°F (10°C) - 80°F for maximum efficiency. Spreading rate to approximate 1200 lineal feet of standard 4" stripe per gallon will result in a dry film thickness of 2 mils (allowing 20% loss for spraying).

**Asphalt:** May be applied directly to surface. Allow new asphalt to cure a minimum of two weeks before painting.

## Application Equipment

**Brush:** Not recommended due to quick dry times

**Roller/Pad:** Not recommended due to quick dry times

**Airless Spray:** Spray with a .215 tip (or the equivalent 1704 traffic striping tip) to achieve a 4" line, or refer to tip manufacturers recommendation chart.

## SAFETY PRECAUTIONS

*For detailed information please refer to MSDS*

## Recent Amendments

Check for recent amendments to this data sheet at [www.rodmapaint.com](http://www.rodmapaint.com)

**Last Modification date:** 04/06/2016

## Limitation of Liability

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

## WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

**READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.**

