

## Logwood Oil

716479

### DESCRIPTION

Logwood Oil is a clear slow drying, oil modified alkyd coating.

### RECOMMENDED USES

Logwood Oil is a clear coating for peeled logs or log homes. It is used as a protective coating against moisture absorption, checking, splitting, and excessive darkening of wood.

### TECHNICAL CHARACTERISTICS

Bases	VOC(g/L)*
Clear Sealer (716479)	442 g/L

*\*Before thinning and colorants*

### TINTING TYPE

This sealer is not formulated for tinting.

### FINISH

Gloss: Gloss will vary with film build.

Sheen: Sheen will vary with film build.

### SOLIDS & DENSITY

Volume: 45.54 %

Weight: 51.70 %

Density: 7.60 lbs per gallon

### FILM THICKNESS (PER COAT)

Wet: 4.0 mils - mils

Dry: 1.80 mils - mils

### THEORETICAL COVERAGE (PER COAT):

theoretical coverage for one mil is 721 sq ft per gallon

### VISCOSITY

52 KU - 58 KU KU

### DRYING TIME

at 77°F and 50% Relative Humidity

Dry to touch: 2 to 4 hours

Dry to recoat: 24 hours

### THINNER

None recommended

### CLEAN UP

Clean Up:

Use the recommended thinner for this coating for clean up: Synthetic Reducer (799260).

### STORAGE TEMPERATURE

Storage Temperature:

40-90 degrees F. Store indoors and keep from freezing.

### SHELF LIFE

minimum two years in unopened containers stored at 70 degrees F.

## SURFACE PREPARATION

All surfaces to be painted must be clean and dry. Special attention should be taken to ensure that all surfaces are free of mold or fungus growth.

## APPLICATION

Gloss will vary with film build (number of coats applied). Do not apply when surface or air temperature are expected to fall below 45 degrees F. before the coating is dry.

### Application Equipment

**Brush:** Use a good quality pure bristle brush.

**Airless Spray:** Pressure 2,000 psi. Tip: .013" to .017".

## SAFETY PRECAUTIONS

*For detailed information please refer to MSDS*

### Warning

**Safety Precautions:** For detailed information please refer to this product's material safety data sheet. A copy of which may be found at our website: [www.rodmapaint.com](http://www.rodmapaint.com) under Products:Product Data Sheets and MSDS.

**Flammable & Combustible:** Use only in a well ventilated area. Keep away from potential sources of flames or sparks, such as a pilot light on a furnace or an electric motor. Keep out of reach of children. Materials such as rags that are used with this product may begin to burn by themselves. After using, completely immerse used rags in water or lay them out flat separately to dry and then discard.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.

### Recent Amendments

Check for recent amendments to this data sheet at [www.rodmapaint.com](http://www.rodmapaint.com)

**Last Modification date:** 03/30/2016

### Limitation of Liability

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

## WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

**READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.**