

Modern Wood Stain

Interior Penetrating Wood Stains 716001



COMPLIANCE INDICATORS

at

MPI #90

DESCRIPTION

Modern Wood Stain is a professional interior semi-transparent alkyd wiping stain and finish for wood. Modern Wood Stain penetrates and seals the wood's surface, providing a rich color that enhances the natural beauty of the wood without raising the grain. Formulated for use on new or bare interior wood surfaces, or to re-stain and refresh existing stained woods with proper preparation.

RECOMMENDED USES

A traditional wiping stain is a slower drying stain providing color control with a beautiful rich finish. Rodda's Modern Wood Stain line is formulated to stain & finish in one step, and additional colors can be applied for special effects and custom shading. Ideal for use on cabinets, woodwork, paneling, doors, furniture and floors, and can be custom tinted to desired colors.

FEATURES

- plenty of "open" time to work with the wiping stain to achieve the look you want
- wiping stain for interior wood surfaces such as woodwork, furniture, cabinets, or doors
- use with MWS sealer for new wood or hard to stain grains
- available in white for 'pickling' projects and bases for color tones

TECHNICAL CHARACTERISTICS

Bases	VOC(g/L)*
White Base (716001)	524 g/L or 4.37 lb per gallon
Deep Base (716003)	524 g/L
Neutral Base (716004)	543 g/L

*Before thinning and colorants

TINTING TYPE

Universal Tinting Colorant

FINISH

Gloss: None

Sheen: None

SOLIDS & DENSITY

Volume: 32 %

Weight: 51 %

Density: 8.90 lbs per gallon

FILM THICKNESS (PER COAT)

Wet: refer to coverage value - mils

Dry: immeasurable - mils

VISCOSITY

50 KU - 55 KU KU

DRYING TIME

at 77°F and 50% Relative Humidity

to wipe: 10 minutes: less or more time may be needed based on wood porosity and look desired

Dry time to recoat: 16 to 24 hours

THINNER

none needed

CLEAN UP

Use the recommended thinner for this paint for clean up: Mineral Thinner (799250).

STORAGE TEMPERATURE

40-90 degrees F. Store indoors and keep from freezing.

SHELF LIFE

minimum of two years stored in unopened cans at 70 degrees F.

SURFACE PREPARATION

New or Bare Wood (Interior): Sand to remove mill glaze to expose fresh wood cells prior to applying paint or stain. Remove sanding dust prior to application of stain.

Application Equipment

Brush: Use a good quality pure bristle brush.

Roller: Use a 1/4"--a longer nap synthetic cover may be needed depending on the degree of texture of the surface to be painted.

SAFETY PRECAUTIONS

For detailed information please refer to MSDS

Warning

Safety Precautions: For detailed information please refer to this product's material safety data sheet. A copy of which may be found at our website: www.rodmapaint.com under Products:Product Data Sheets and MSDS.

Flammable & Combustible: Use only in a well ventilated area. Keep away from potential sources of flames or sparks, such as a pilot light on a furnace or an electric motor. Keep out of reach of children. Materials such as rags that are used with this product may begin to burn by themselves. After using, completely immerse used rags in water or lay them out flat separately to dry and then discard.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.

Recent Amendments

Check for recent amendments to this data sheet at www.rodmapaint.com

Last Modification date: 02/24/2016

Limitation of Liability

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.