



WALL PRO

PROCOAT PLUS PVA PRIMER

High Quality Interior Waterborne Wallboard Primer
(4034B Series)

DESCRIPTION

ProCoat PLUS PVA Primer is a high quality, interior, waterborne, production grade, PVA latex WALLBOARD primer to be applied to new drywall or after the application of wall-textures.

ProCoat PLUS PVA Primer is part of the Wall Pro paint system, formulated for new, residential and commercial construction projects and is applied to minimize visual surface differences between tape joints and sheetrock papers, helping to insure a uniform surface ready for finish coats.

ProCoat PLUS PVA Primer is low VOC and easy to apply with mild odor and good sealing properties to lay-down drywall paper fuzz for smooth topcoats. ProCoat PLUS PVA Primer dries quickly for better production work scheduling and cleans-up easily with warm water.

ProCoat PLUS PVA Primer combined with Wall Pro Interior Paint, provides an excellent value priced finishing system for new construction. ProCoat PLUS PVA Primer is most often sprayed, but, it can also be brushed or rolled and then top-coated with a Rodda Paint waterborne or alkyd interior paint.

RECOMMENDED USES

ProCoat PLUS PVA Primer is the preferred choice for sealing new, smooth or textured interior sheetrock before top-coating finish applications on new, commercial and residential projects.

DO NOT use directly over masonry, metal, wood, or previously painted surfaces. Ideal for Residential and Commercial projects.

AVAILABILITY

Available in 5 gallon pails, 55 gallon drums and 250 gallon totes

TECHNICAL CHARACTERISTICS

| Bases | VOC (g/L)* |
|-------------------------|------------|
| White (4034B01) | <75.0 g/L |
| Cascade White (4034B11) | <75.0 g/L |

**Before thinning and colorants*

TINTING TYPE

Universal Tinting Colorant

FINISH

Gloss: 0.50 to 1.50

Sheen: 1 to 2

SOLIDS & DENSITY

Volume: 33%

Weight: 55%

Density: 11.20 lbs per gallon

FILM THICKNESS (PER COAT)

Wet: 5 - 6 mils

Dry: 1.5 - 2 mils

THEORETICAL COVERAGE (PER COAT):

529 Sq. ft. per gallon at 1.0 mil dry film thickness

Actual coverage dependent on surface profile, mil thickness, application technique and type of spray tip/amount of fallout

VISCOSITY

100 – 105 KU

DRYING TIME at 77°F and 50% Relative Humidity:

Dry to touch: 30 minutes

Dry to recoat: 2 hours

THINNER

NONE recommended

CLEAN UP

After use, clean application tools with warm soapy water and rinse thoroughly.

STORAGE TEMPERATURE

Store indoors at 40-90F

KEEP FROM FREEZING!

SHELF LIFE

12 months in unopened containers.





SURFACE PREPARATION

Surface preparation is important. All surfaces must be of uniform porosity, smooth, clean, dry and free of mildew, grease, soap-film, sanding dust or other contaminants. Wash with a cleaner/mild detergent & water solution, rinse thoroughly and allow to dry. Ensure all substrates to be coated are free of mildew, mold, algae or other biological contaminants. Repair all cracks, holes and voids with an elastomeric patch or elastomeric caulk/sealant.

Glossy/smooth surfaces should be dulled or scuff/ sanded using 120 grit sandpaper.

Remove all sanding dust prior to painting. Apply a test patch of paint to questionable areas to check for adhesion prior to painting.

APPLICATION EQUIPMENT

Brush: Use a good quality nylon/ polyester brush.

Roller: Use a 3/8" – 3/4" nap synthetic cover depending on the degree of texture of the surface to be painted.

Airless Spray: Pressure 2,000 psi. Tip: .017 – .021.

SAFETY PRECAUTIONS

Warning: Use only with adequate ventilation. Keep container closed when not in use. Do not transfer contents to other containers for storage.

Avoid inhalation of dust, vapors or spray mist. Prolonged exposure to or repeated breathing of spray/mists can cause respiratory irritation. Wash thoroughly after handling. Wear eye protection, protective gloves, protective clothing. Use appropriate personal safety equipment.

First Aid: In case of eye contact, flush with plenty of water for 15 minutes. If skin or eye irritation persists, get medical attention. If you experience breathing difficulty, leave the area to obtain fresh air. If irritation persists/difficulty continues, get medical assistance immediately. If ingested, call physician or the Poison Control Center immediately

Safety Precautions: For detailed information please refer to this product's Safety Data Sheet (SDS) - Please obtain a copy of the SDS document from your Rodda Paint Sales Rep/Store.

REGULATORY

This product is not considered a hazardous waste Under Current RCA regulations. This product does not contain, nor is it manufactured using ozone-depleting substances as listed under Section 611 of the Clean Air Act.

WARRANTY

The information and recommendations contained on the product labels and in this product bulletin are offered by to the best of our knowledge, accurate and reliable. No guarantee is made of their accuracy, however, the products discussed are sold upon condition that the purchaser/customer shall make their own tests to determine the suitability of this product for their particular purposes and uses. Nothing in bulletins or on labels constitutes permission or a recommendation to practice or use any invention covered by any patent by any company or person. Our liability will be limited to replacement of merchandise found to be defective by the company representatives. The manufacturer shall not be liable for any representations (express or implied) made by any of its agents, representatives or employees regarding its merchandise or other warranties.

READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.

