


# Wood Master

**Interior Gloss Level 4 Low Gloss Enamel  
533590**



## COMPLIANCE INDICATORS

## DESCRIPTION

Rodda's Woodmaster are super-premium, 100% acrylic, interior waterborne enamels formulated without compromise to provide exceptional performance and durability. The Woodmaster enamel family has two designer sheens with great adhesion over aged-alkyds. The cross-linking acrylic formula provides exceptional blocking and fade resistance with great touch-up properties, but remains flexible for applications on doors, siding, fascia and trim. Woodmaster enamels are stain and mildew resistant, easily washable and resist cracking and deterioration with age for greater long-term service life. Woodmaster flows easily with little brush-drag, are self-leveling to a smooth finish and dry quickly, yet clean-up easily with warm water. The non-yellowing technology in Woodmaster enamel is a smart choice for interior millwork, when an exceptional finish is desired, and also mold and mildew resistant making it ideal for wet room work.

## RECOMMENDED USES

Woodmaster enamels are an excellent choice for the discriminating buyer for all residential, commercial and institutional painting projects, or whenever a durable enamel finish is desired. Woodmaster provides superior performance on all interior surfaces, can be brushed, rolled or sprayed onto drywall and plaster, high traffic areas, doors and trim or over masonry and primed metals using Rodda's premium primers, Scotseal, Unique II Enamel Undercoater, or First Coat. The versatile Woodmaster family includes a low gloss and semi-gloss enamel is backed by the Rodda Paint Warranty for interior applications (see your Rodda Sales Rep or Store Manager for details), and available in one gallon cans and five gallon pails. Woodmaster is supported by a selection of our 1320+ colors in Rodda's "Color Right" system, the majority of our exclusive Cascadia colors of the Northwest neighborhoods and can be custom-matched to most any white or lighter color tone.

## TECHNICAL CHARACTERISTICS

Bases	VOC(g/L)*
White Base (533590)	<200 g/L (1.67 lbs/gal)

\*Before thinning and colorants

## TINTING TYPE

Universal Tinting Colorant

## FINISH

Gloss: 25 to 35

Sheen: 65 to 75

## SOLIDS & DENSITY

Volume: 36%

Weight: 48%

Density: 10.60 lbs per gallon

## FILM THICKNESS (PER COAT)

Wet: 4.0 - mils

Dry: 1.50 - mils

## THEORETICAL COVERAGE (PER COAT):

562 sq ft for 1.0 mils dry film thickness

## VISCOSITY

98 - 102 KU

## DRYING TIME

at 77°F and 50% Relative Humidity

Dry to touch: 1/2 hour

Dry to recoat: 2 hours

## THINNER

Normally thinning is not required. In hot weather clean tap water may be used.

## CLEAN UP

After use, clean application tools with warm soapy water and rinse thoroughly.

## STORAGE TEMPERATURE

40-90 degrees F. Store indoors and keep from freezing.

## SHELF LIFE

minimum 2 years in unopened containers with correct storage

## SURFACE PREPARATION

**Surface preparation is important.** All surfaces must be smooth, clean, dry, free of mildew, grease, chalk, soap film, sanding dust or other contaminants. Remove all loose or peeling material from previously-painted surfaces. Wash with a mild detergent and water solution. Rinse thoroughly, allow to dry. On exterior surfaces after cleaning, check for chalk ( paint oxidation) on the surfaces with a dark colored rag. If chalk is still present re-wash affected surfaces. If needed on glossy or smooth surfaces: scuff sand using 80-120 grit sandpaper. Remove all sanding dust prior to painting. Do not apply at ambient temperatures below 50°F (10°C).

**New or Bare Wood (Interior):** Sand to remove mill glaze to expose fresh wood cells prior to applying paint or stain. Remove sanding dust prior to application of sealer or primer.

**Surface Prep for Unpainted Concrete:** Remove all surface contamination, form release agents, moisture curing membranes, mildew, efflorescence, etc. by pressure washing with an appropriate cleaner. Then rinse and allow to dry. Do not apply to damp or wet surfaces. Concrete or mortar needs to be cured approximately 30 days at 70 degrees F. Do not apply block filler to smooth surfaces as peeling may occur.

**Pre-Painted Surfaces:** Wash with a mild detergent and water solution. Rinse thoroughly, allow to dry, and then, if needed due to a glossy or hard smooth surface: scuff sand using 80 to 120 grit sandpaper on a hand sander. Remove all sanding dust.

**WARNING!** If you scrape, sand or remove old paint from any surface you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. For additional information on surfaces that may contain lead paint, contact the U.S. EPA / Lead Information Hotline at 1-800-424-LEAD (5323).

## APPLICATION

When deciding to paint vinyl siding, care must be taken not to use a darker colored paint than the original color of the siding as this can cause the surface to become very hot in the summer sun and lead to warping of the siding.

### Application Equipment

Brush: Use a good quality nylon/ polyester brush.

Roller: Use a 3/16" - 3/8" nap synthetic cover depending on the roughness of the surface to be painted.

Airless Spray: Pressure 2,000 psi. Tip: .015" to .019"

## SAFETY PRECAUTIONS

*For detailed information please refer to MSDS*

### Warning

For detailed information please refer to this product's material safety data sheet. A copy of which may be found at our website: [www.rodmapaint.com](http://www.rodmapaint.com) under Products:Product Data Sheets and MSDS.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.

### Recent Amendments

Check for recent amendments to this data sheet at [www.rodmapaint.com](http://www.rodmapaint.com)

**Last Modification date:** 08/03/2016

### Limitation of Liability

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

## WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

## READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.



# TECHNICAL DATA SHEET



Rodda Paint Company  
6107 North Marine Drive, Portland, Oregon, USA 97203  
Corporate Office 1.800.452.2315  
[www.rodmapaint.com](http://www.rodmapaint.com)



Formulated and Manufactured  
in Portland, Oregon, USA

Page 3 of 3  
Product: 533590  
Printed: 04/07/2020  
Version: 08/03/2016