

WALL PRO

Interior Gloss Level 3 Eggshell Finish
533401

COMPLIANCE INDICATORS

DESCRIPTION

Rodda Paint's WallPro Series is designed for professional painters for interior production and maintenance projects. The high-build formula technology provides exceptional coverage with great flow and leveling properties. The Ultra-low VOC content has virtually no odor, making application safer for indoor air quality, the environment, employees and clients. WallPro products are spatter-resistant, easy to apply with good brush and roller workability and provide great washability for interior facility maintenance applications. The top coats can be tinted to support the Rodda Paint ColorRight system and can be tinted to match most competitor colors for applications on drywall, plaster, interior doors and trim. WallPro products are available in one gallon and five gallon pails and will clean-up easily in water.

RECOMMENDED USES

The WallPro family of products are designed for new interior construction projects, facilities and property maintenance, and other production application projects where high hide and low odor are required. WallPro is a great choice for new residential work, new commercial construction and works well for apartment and facility maintenance projects.

FEATURES

- For use on interior wall surfaces including drywall and plaster
- May be used over interior primed wood
- Can be applied up to 18 wet mils without runs or sags
- Formulated for low spatter when using roller application
- Dries fast and has excellent touch-up properties

TECHNICAL CHARACTERISTICS

Bases	VOC(g/L)*
White Base (533401)	<0.5 g/L (0.00 lbs/gal)

*Before thinning and colorants

TINTING TYPE

Zero VOC or Universal Tinting Colorant

FINISH

Gloss: 11 to 16

Sheen: 23 to 29

SOLIDS & DENSITY

Volume: 40.0 %

Weight: 50.5 %

Density: 10.42 lbs per gallon

FILM THICKNESS (PER COAT)

Wet: 4.0 - mils

Dry: 1.50 - mils

THEORETICAL COVERAGE (PER COAT):

theoretical coverage for 1.0 mil dry film thickness is 642 sq ft per gallon

VISCOSITY

94 - 101 KU

DRYING TIME

at 77°F and 50% Relative Humidity

Dry to touch: 30 minutes

Dry to recoat: 2 hours

THINNER

none normally required

CLEAN UP

After use, clean application tools with warm soapy water and rinse thoroughly.

STORAGE TEMPERATURE

40-90 degrees F. Store indoors and keep from freezing.

SHELF LIFE

two years when stored in unopen containers at 70 degrees F.

SURFACE PREPARATION

Surface preparation is important. All surfaces must be smooth, clean, dry, free of mildew, grease, chalk, soap film, sanding dust or other contaminants. Remove all loose or peeling material from previously-painted surfaces. Wash with a mild detergent and water solution. Rinse thoroughly, allow to dry. If needed on glossy or smooth surfaces: scuff sand using 80-120 grit sandpaper. Remove all sanding dust prior to painting. Do not apply at ambient temperatures below 50°F (10°C).

New or Bare Wood (Interior): Sand to remove mill glaze to expose fresh wood cells prior to applying paint or stain. Remove sanding dust prior to application of sealer or primer.

Drywall (Interior): Self-priming with 2 coats of Wall Pro Eggshell Latex.

WARNING! If you scrape, sand or remove old paint from any surface you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. For additional info on surfaces that may contain lead paint, contact the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323).

Application Equipment

Brush: Use a good quality nylon/ polyester brush.

Roller: Use a 3/8" -1/2" nap synthetic cover depending on the degree of texture of the surface to be painted.

Airless Spray: Pressure 2,000 psi. Tip: .015" to .021".

SAFETY PRECAUTIONS

For detailed information please refer to MSDS

Warning

Safety Precautions: For detailed information please refer to this product's material safety data sheet, a copy may be found at our website: www.rodmapaint.com under Products:Product Data Sheets and MSDS.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.

Recent Amendments

Check for recent amendments to this data sheet at www.rodmapaint.com

Last Modification date: 10/11/2016

Limitation of Liability

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.