

TECHNICAL DATA SHEET

WALL PRO Interior Prep Hi Hide Primer - Cascade White 503411

COMPLIANCE INDICATORS

DESCRIPTION

Wall Pro Hi Hide Prep is an interior vinyl latex wall primer tinted to Cascade white.

RECOMMENDED USES

Wall Pro prep is for priming and sealing new or previously painted drywall. Formulated for use as an interior primer under latex topcoats on sheetrock and plaster walls and ceilings.

FEATURES

- HI Hide formulation
- Applies easily
- Dries quickly
- Water clean up

TECHNICAL CHARACTERISTICS

sases VOC(g/L)*

HiHide Cascade White

49.00g/L (0.41 lbs/gal)

(503411)

*Before thinning and colorants

TINTING TYPE

Universal Tinting Colorant for pastel colors only

FINISH

Gloss: 0.50 to 1.50 Sheen: 1 to 2

SOLIDS & DENSITY

Volume: 33.0 % Weight: 49.0 %

Density: 11.46 lbs per gallon

FILM THICKNESS (PER COAT)

Wet: 4 - mils Dry: 1.20 - mils

THEORETICAL COVERAGE (PER COAT):

theoretical coverage for 1.0 mil dry film thickness is 535

sq ft per gallon

VISCOSITY

98 - 102 KU

DRYING TIME

at 77°F and 50% Relative Humidity Dry to touch: 30 minutes

Dry to recoat: 2 hours

THINNER

none recommended

CLEAN UP


After use, clean application tools with warm soapy water and rinse thoroughly.

STORAGE TEMPERATURE

40-90 degrees F. Store indoors and keep from freezing.

SHELF LIFE

two years in unopened containers at 70 degrees F.





TECHNICAL DATA SHEET

SURFACE PREPARATION

Surface preparation is important. Remove all loose or peeling material from previously-painted surfaces. Wash with a mild detergent and water solution. If needed on glossy or smooth surfaces: scuff sand using 80-120 grit sandpaper. Remove all sanding dust prior to painting. Do not apply at ambient temperatures below 50°F (10°C).

Application Equipment

Brush: Use a good quality nylon/ polyester brush.

Roller: Use a 1/4" -3/8" nap synthetic cover depending on the degree of texture of the surface to be painted.

Airless Spray: Pressure 2,000 psi. Tip: .015" to .021".

SAFETY PRECAUTIONS

For detailed information please refer to MSDS

Warning

Safety Precautions: For detailed information please refer to this product's material safety data sheet. A copy of which may be found at our website: www.roddapaint.com under Products:Product Data Sheets and MSDS.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.

Recent Amendments

Check for recent amendments to this data sheet at www.roddapaint.com

Last Modification date: 09/26/2017

Limitation of Liability

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.



