

# **TECHNICAL DATA SHEET**

# WALL PRO

**Interior Prep Pre-Texture Primer** 503409

#### **COMPLIANCE INDICATORS**

#### **DESCRIPTION**

Wall Pro Prep is an interior acrylic (PVA) Latex Primer.

# **RECOMMENDED USES**

Wall Pro Prep is a prior-to-texturing drywall primer to minimize visual difference between wall surfaces with taping compound (joints) and sheetrock wall surfaces after finish coat is applied. This primer will give the entire wall surfaces the same porosity and will allow the texture to dry the same over joints and wallboard. Therefore, the texture pattern will be the same depth over the entire surface.

#### **FEATURES**

- low VOC's
- fast drying
- applies easily

## **TECHNICAL CHARACTERISTICS**

Bases VOC(g/L)\*

Prep (503409) <50.00g/L (0.42 lbs/gal)

\*Before thinning and colorants

#### TINTING TYPE

This coating is not formulated for tintability.

#### **FINISH**

Gloss: 0.50 to 1.50 Sheen: 1.0 to 2.0

#### **SOLIDS & DENSITY**

Volume: 26.0 % Weight: 44.0 %

Density: 10.98 lbs per gallon

# FILM THICKNESS (PER COAT)

Wet: 5.0 - mils Dry: 1.20 - mils

# THEORETICAL COVERAGE (PER COAT):

theoretical coverage for one mil dry film thickness is 401 sq ft per gallon

# VISCOSITY

90 - 92 KU

#### **DRYING TIME**

at 77°F and 50% Relative Humidity

Dry to touch: 30 minutes Dry to recoat: 2 hours

## **THINNER**

none recommended

# **CLEAN UP**

After use, clean application tools with warm soapy water and rinse thoroughly.

## STORAGE TEMPERATURE

40-90 degrees F. Store indoors and keep from freezing.

#### SHELF LIFE

two years when stored in closed containers at 70 degrees  ${\sf F.}$ 







# TECHNICAL DATA SHEET

#### SURFACE PREPARATION

Remove all sanding dust prior to painting. Do not apply at ambient temperatures below 50°F (10°C).

## **Application Equipment**

**Brush:** Use a good quality nylon/ polyester brush. **Roller:** Use a 1/4" -3/8" nap synthetic roller cover. **Airless Spray:** Pressure 2,000 psi. Tip: .015" to .021".

#### SAFETY PRECAUTIONS

For detailed information please refer to MSDS

Warning

**Safety Precautions:** For detailed information please refer to this product's material safety data sheet. A copy of which may be found at our website: www.roddapaint.com under Products:Product Data Sheets and MSDS.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.

.

#### **Recent Amendments**

Check for recent amendments to this data sheet at www.roddapaint.com

Last Modification date: 01/13/2017

#### **Limitation of Liability**

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

#### WARRANTY

Rodda Paint warrants its product to be free from defects in materials and workmanship and will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE, OR REFUND OF THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED TO BE DEFECTIVE. Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for his own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

#### READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.



