

TECHNICAL DATA SHEET

Commercial · Industrial · Residential

Professional Strength Coatings Stripper

SHARKSKIN® - DECK & SIDING STRIPPER

(80318)

DESCRIPTION

SHARKSKIN Deck & Siding Stripper is a highly concentrated, alkaline formulation manufactured to quickly remove old and worn stains, solid color, oil based stains, latex paint, and sealers from wood surfaces prior to the application of new finishes.

SHARKSKIN Deck Stripper will also degrease and clean while removing damaged and discolored wood fiber from all exterior wood surfaces, decks, wood siding and log homes.

FEATURES/BENEFITS:

- Removes paint and stain from wood surfaces
- Removes damaged and discolored wood fibers
- Cleans and degreases while it strips away coating
- Fast acting concentrated formula
- · Thickened formula clings to surfaces

TECHNICAL DATA

SKU #	80318
Solubility in Water	Complete
рН	12-14
Specific Gravity	1.10-1.20
Appearance	Clear slightly thick red liquid
Odor	Chemical odor
Flammability	N/A
Protective Equipment	Neoprene Gloves & Goggles
Container Size	1 gallon
Coverage	150-1000 sq ft, Depending on application

DIRECTIONS FOR USE:

- Dilute SHARKSKIN Deck Stripper with water at a 1:1 or 1:2 ratio subject to conditions, to remove most stains and sealers from wood.
- Apply with a pump up sprayer and wait 15-30 minutes, or until coating softens or dissolves.
- Use a stiff bristle brush to remove residue from surface.
- Rinse using a garden hose or pressure washer at a low pressure setting.
- For solid finishes product may need to be used without dilution.

WARNINGS:

- Do not allow product to dry on surface
- Protect metal and glass from contact
- Thoroughly wet surrounding vegetation
- Contains sodium hydroxide, potassium hydroxide and other alkaline materials
- Always test in an inconspicuous area first

WARNING! If you scrape, sand or remove old paint from any surface you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN.

PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a **NIOSH** approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. For additional information on surfaces that may contain lead paint, contact the U.S. EPA / Lead Information Hotline at **1.800.424.LEAD (5323)**.

SAFETY PRECAUTION

For detailed information please refer to this product's safety data sheet (SDS) – A copy of which can be found on our website, www.roddapaint.com under Products/Product Data Sheets and SDS

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Center immediately.







TECHNICAL DATA SHEET

Commercial · Industrial · Residential

LIMITATION OF LIABILITY

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis.

They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

WARRANTY

Rodda Paint Co. manufactures quality products and warrants its product to be free from defects in materials and workmanship. In the event that this product is defective or in any way unsuitable for the application for which it was sold, Rodda Paint Co. will REPLACE ANY PRODUCT PROVED TO BE DEFECTIVE free of charge OR REFUND THE ORIGINAL PURCHASE PRICE OF THE QUANTITY PROVED. This warranty is the only guarantee of quality made in respect of this product by Rodda Paint Co. By purchasing this product the customer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the customer or implied by any applicable law.

TO BE DEFECTIVE – Requests for refund or replacement of product must be made in writing within one year from the original date of purchase. This Warranty does not apply to defects due, directly or indirectly, to misuse, abuse, negligent application, or acts of God.

Rodda Paint. WILL NOT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCT, INCLUDING DOWNTIME OR LOSS OF USE OF PRODUCT.

All data, statements, and recommendations made herein are based upon information we believe to be reliable, but, are made without any representation, guarantee or warranty of accuracy. Our products are sold on the condition that the user themselves will evaluate them, as well as our recommendations, to determine the suitability for their own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

See your Rodda Sales Rep or Store Manager for details.

READ LABEL AND SAFETY DATA SHEET PRIOR TO USE!



