

COMMERCIAL • INDUSTRIAL • RESIDENTIAL

Interior/Exterior Acrylic Enamel

Waterborne Acrylic Latex



- Outstanding Block Resistance & Touch-Up
- Exceptional Hide & Coverage
- Superior Gloss & Color Retention
- Low Odor During Application
- Stain & Mildew Resistant



A Proven Performer that EXCEEDS Expectations on Delivering a Quality Finish!



The Rodda Paint Difference



Unique II Interior/Exterior Acrylic Enamels provide High Performance & Versatility that Resists Cracking and Deterioration with Age - A Proven Performer for Long-Term Service Life and Color Retention!

Description:

Unique II is a premium, 100% acrylic, interior/exterior enamel delivering high performance and versatility...A Proven Performer that EXCEEDS expectations on delivering a Quality Finish!

Formulated for excellent adhesion with outstanding block resistance and touch-up properties, Unique II Low VOC enamels provide exceptional hide, coverage and gloss & color retention, as well as low odor during application with minimal spatter. Additionally, Unique II Low VOC enamels are stain & mildew resistant, easily washable and resist cracking & deterioration with age for greater long-term service life.

While the Unique II Low Gloss/**GL4** and SemiGloss/**GL5** are **Low VOC** formulas, **all 3** Unique II finishes are designed to offer superior <u>interior</u> performance, including over aged alkyds, yet remain flexible for <u>exterior</u> application on doors, siding, fascia & trim and can be applied down to 40F.

Unique II Low VOC enamels are easy to apply with a brush, roller or sprayer and can be complimented with the Unique II Enamel Undercoater for a durable finish on woodwork.

"Unique II is a fantastic product for interior and exterior use. It brushes and rolls nicely and lays out really smooth."

- Anonymous Customer 1

Recommended Uses:

- Designed for Professional Contractors and DIYers alike looking for a premium, durable enamel finish for usage on all interior & exterior surfaces such as, properly prepared & primed wood, trim, siding, masonry, brick, concrete, cement, stucco, plaster, EFIS, fiber cement composite, gypsum wallboard, vinyl and prepainted aluminum siding
- Can also be used on properly primed metal surfaces like gutters and downspouts
- Great choice for high traffic areas, kitchen & bathroom walls, millwork & doors, including front doors & trim
- MPI approved and Exceptionally suited for commercial projects where formal industry quality approvals are required
- An excellent choice for all residential and commercial painting projects
- Versatile and efficient for Commercial Property Maintenance

"This is a great product for painting front/exterior doors. Over time, Unique II resists cracking in the elements and its color retention is unrivaled."

- Anonymous Customer 2

Unique II Technical Data

Sheen	Gloss Level	Base	MPI Approved	voc	Volume Solids	Film Thickness		Reducers	Minimum Application	Application and Curing at 77F and 50% Relative	Application
						Wet	Dry	reducer 3	Temperature	Humidity	Recommendation
Low Gloss	4	White, Deep, Neutral	15	< 50 g/L	36% (Varies by Base)	4.4-6.0 mils	1.5-2.0 mils	Not normally recommended. Reduce sparingly	40F	Dry to Touch: 30 min Dry to Recoat: 8 hrs	Nylon/Polyester Brush 1/4" to 3/4" Nap Synthetic Roller Cover
Semi Gloss	5	White, Deep, Neutral	11, 141		35% (Varies by Base)						
Gloss	6	White	114, 119	<150 g/L	34% (Varies by Base)		with water for spray applications			2000 psi Pressure Airless	
Undercoater/ Interior Primer	0	White	39	< 80 g/L	39	4.0 mils	1.5 mils		50F	Dry to Touch: 30 min Dry to Recoat: 2 hrs	Spray with .015019 tip

For additional details please see your Rodda Representative for the Technical Data Sheet (TDS) for this product.

Quality, Tradition, Trust Since 1932



6107 N. Marine Drive, Portland, OR 503-521-4300 | 800-452-2315 RoddaPaint.com | Follow Us ☐ ☑ In ☑ ► Ask your Rodda Paint representative about the Cascadia Color Collection, a nature inspired color palette.

