

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : BARRIER III HS PRIMER GRAY
 Product code : 708298

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Rodda Paint Co.
 6107 North Marine Drive
 Portland, Oregon 97203 - US
 T (503) 521-4300
www.rodmapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, Category 2	Highly flammable liquid and vapour
Sensitisation — Skin, Category 1	May cause an allergic skin reaction
Germ cell mutagenicity, Category 1B	May cause genetic defects
Carcinogenicity, Category 1B	May cause cancer
Hazardous to the aquatic environment — Acute Hazard, Category 3	Harmful to aquatic life

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapour
 May cause an allergic skin reaction
 May cause genetic defects
 May cause cancer
 Harmful to aquatic life

Precautionary statements (GHS-US) :

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 Keep container tightly closed
 Ground/Bond container and receiving equipment
 Use explosion-proof electrical, lighting, ventilating equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Avoid breathing dust, fume, gas
 Contaminated work clothing must not be allowed out of the workplace
 Avoid release to the environment
 Wear eye protection, face protection, protective clothing, protective gloves
 If on skin: Wash with plenty of soap & water
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If exposed or concerned: Get medical advice/attention
 Specific treatment (see In all cases of doubt, or when symptoms persist, seek medical attention, Seek medical attention if irritation develops on this label)
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

In case of fire: Use ABC-powder, dry sand, foam to extinguish
Store in a well-ventilated place. Keep cool
Store locked up
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
TALC substance with OEL values	(CAS No) 14807-96-6	12	Not classified
METHY N-PROPYL KETONE	(CAS No) 107-87-9	7.9	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302
VM&P NAPHTHA	(CAS No) 8032-32-4	7.7	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
TITANIUM DIOXIDE	(CAS No) 13463-67-7	5.4 - 7.1	Carc. 2, H351
METHYL ETHYL KETONE substance with OEL values	(CAS No) 78-93-3	4.2	Flam. Liq. 2, H225 STOT SE 3, H336
SOLVENT NAPHTHA, LIGHT AROMATIC	(CAS No) 64742-95-6	1.6	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
N-BUTYL ACETATE substance with OEL values	(CAS No) 123-86-4	1	Flam. Liq. 2, H225 STOT SE 3, H336
MIBK	(CAS No) 108-10-1	0.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Carc. 2, H351 STOT SE 3, H335
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	(CAS No) 64742-48-9	0.5	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
MINERAL SPIRITS	(CAS No) 64741-65-7	0.3	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
METHYL ETHYL KETOXIME	(CAS No) 96-29-7	0.2	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
ETHYLBENZENE	(CAS No) 100-41-4	0.2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
CARBON BLACK	(CAS No) 1333-86-4	0.1	Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
Reactivity : Highly flammable liquid and vapour.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

METHYL ETHYL KETOXIME (96-29-7)		
AIHA	WEEL TWA (ppm)	10 ppm
VM&P NAPHTHA (8032-32-4)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³
TALC (14807-96-6)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
IDLH	US IDLH (mg/m ³)	1000 mg/m ³ (containing no asbestos and <1% quartz)
NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
METHYL ETHYL KETONE (78-93-3)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	300 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	3000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	885 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	300 ppm
CARBON BLACK (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
IDLH	US IDLH (mg/m ³)	1750 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)
MINERAL SPIRITS (64741-65-7)		
Not applicable		
ETHYLBENZENE (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)		
Not applicable		
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Not applicable		

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHY N-PROPYL KETONE (107-87-9)		
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	700 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	1500 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	530 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
MIBK (108-10-1)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
ACGIH	Remark (ACGIH)	URT irr; dizziness; headache
OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	205 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	300 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	75 ppm
N-BUTYL ACETATE (123-86-4)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
IDLH	US IDLH (ppm)	1700 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	710 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	950 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	200 ppm
TITANIUM DIOXIDE (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
IDLH	US IDLH (mg/m ³)	5000 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Personal protective equipment

: Gloves. Respiratory protection of the dependent type. Protective goggles. Protective clothing.



Hand protection

: Protective gloves.

Eye protection

: Safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Wear respiratory protection.

Environmental exposure controls

: Avoid release to the environment.

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Grey
Odour	: aromatic
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Specific gravity	: No data available
Density	: 10.42 lb/gal
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: ≈ 1500 cSt
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

METHYL ETHYL KETOXIME (96-29-7)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
LC50 inhalation rat (mg/l)	> 4800 mg/l (Exposure time: 4 h)

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHYL ETHYL KETOXIME (96-29-7)	
ATE US (oral)	930.000 mg/kg bodyweight
ATE US (dermal)	1000.000 mg/kg bodyweight
VM&P NAPHTHA (8032-32-4)	
LC50 inhalation rat (ppm)	3400 ppm/4h
ATE US (gases)	3400.000 ppmv/4h
METHYL ETHYL KETONE (78-93-3)	
LD50 oral rat	2483 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (ppm)	11700 ppm/4h
ATE US (oral)	2483.000 mg/kg bodyweight
ATE US (dermal)	5000.000 mg/kg bodyweight
ATE US (gases)	11700.000 ppmv/4h
CARBON BLACK (1333-86-4)	
LD50 oral rat	> 15400 mg/kg
MINERAL SPIRITS (64741-65-7)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h
ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE US (oral)	3500.000 mg/kg bodyweight
ATE US (dermal)	15400.000 mg/kg bodyweight
ATE US (gases)	4500.000 ppmv/4h
ATE US (vapours)	17.200 mg/l/4h
ATE US (dust,mist)	1.500 mg/l/4h
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
METHY N-PROPYL KETONE (107-87-9)	
LD50 oral rat	1600 mg/kg
LD50 dermal rat	6480 mg/kg
LC50 inhalation rat (ppm)	2000 ppm/4h
ATE US (oral)	1600.000 mg/kg bodyweight
ATE US (dermal)	6480.000 mg/kg bodyweight
ATE US (gases)	2000.000 ppmv/4h
MIBK (108-10-1)	
LD50 oral rat	2080 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	8.2 mg/l/4h
ATE US (oral)	2080.000 mg/kg bodyweight
ATE US (dermal)	3000.000 mg/kg bodyweight
ATE US (gases)	4500.000 ppmv/4h
ATE US (vapours)	8.200 mg/l/4h
ATE US (dust,mist)	1.500 mg/l/4h
N-BUTYL ACETATE (123-86-4)	
LD50 oral rat	10768 mg/kg

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-BUTYL ACETATE (123-86-4)	
LD50 dermal rabbit	> 17600 mg/kg
LC50 inhalation rat (ppm)	390 ppm/4h
ATE US (oral)	10768.000 mg/kg bodyweight
ATE US (gases)	390.000 ppmv/4h

TITANIUM DIOXIDE (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

TALC (14807-96-6)	
IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

CARBON BLACK (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

ETHYLBENZENE (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

MIBK (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

TITANIUM DIOXIDE (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified
Symptoms/injuries after skin contact : May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

METHYL ETHYL KETOXIME (96-29-7)	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHYL ETHYL KETOXIME (96-29-7)	
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
TALC (14807-96-6)	
LC50 fish 1	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
METHYL ETHYL KETONE (78-93-3)	
LC50 fish 1	3130 - 3320 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	> 520 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	5091 mg/l (Exposure time: 48 h - Species: Daphnia magna)
MINERAL SPIRITS (64741-65-7)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)
ETHYLBENZENE (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
LC50 fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
METHY N-PROPYL KETONE (107-87-9)	
LC50 fish 1	1190 - 1290 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
MIBK (108-10-1)	
LC50 fish 1	496 - 514 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	170 mg/l (Exposure time: 48 h - Species: Daphnia magna)
N-BUTYL ACETATE (123-86-4)	
LC50 fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

METHYL ETHYL KETOXIME (96-29-7)	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)
TALC (14807-96-6)	
BCF fish 1	(no known bioaccumulation)
METHYL ETHYL KETONE (78-93-3)	
Log Pow	0.3
ETHYLBENZENE (100-41-4)	
BCF fish 1	15
Log Pow	3.2
METHY N-PROPYL KETONE (107-87-9)	
Log Pow	0.91
MIBK (108-10-1)	
Log Pow	1.19
N-BUTYL ACETATE (123-86-4)	
Log Pow	1.81 (at 23 °C)

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Waste disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons)

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F)

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

TDG

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ETHYLBENZENE	CAS No 100-41-4	0.2%
METHYL ETHYL KETOXIME (96-29-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA	
VM&P NAPHTHA (8032-32-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
TALC (14807-96-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
METHYL ETHYL KETONE (78-93-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CARBON BLACK (1333-86-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
MINERAL SPIRITS (64741-65-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
ETHYLBENZENE (100-41-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA	
CERCLA RQ	1000 lb	
SARA Section 313 - Emission Reporting	0.1 %	
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
METHY N-PROPYL KETONE (107-87-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
MIBK (108-10-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA	
SARA Section 313 - Emission Reporting	1.0 %	

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-BUTYL ACETATE (123-86-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
CERCLA RQ	5000 lb

TITANIUM DIOXIDE (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

METHYL ETHYL KETOXIME (96-29-7)	
Listed on the Canadian DSL (Domestic Substances List)	

VM&P NAPHTHA (8032-32-4)	
Listed on the Canadian DSL (Domestic Substances List)	

TALC (14807-96-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

METHYL ETHYL KETONE (78-93-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

CARBON BLACK (1333-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

MINERAL SPIRITS (64741-65-7)	
Listed on the Canadian DSL (Domestic Substances List)	

ETHYLBENZENE (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid

METHY N-PROPYL KETONE (107-87-9)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

MIBK (108-10-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

N-BUTYL ACETATE (123-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TITANIUM DIOXIDE (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

EU-Regulations

METHYL ETHYL KETOXIME (96-29-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

VM&P NAPHTHA (8032-32-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

TALC (14807-96-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

METHYL ETHYL KETONE (78-93-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

CARBON BLACK (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on ELINCS (European List of Notified Chemical Substances)

MINERAL SPIRITS (64741-65-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

ETHYLBENZENE (100-41-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

METHY N-PROPYL KETONE (107-87-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

MIBK (108-10-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

N-BUTYL ACETATE (123-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

TITANIUM DIOXIDE (13463-67-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

METHYL ETHYL KETOXIME (96-29-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

VM&P NAPHTHA (8032-32-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TALC (14807-96-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

METHYL ETHYL KETONE (78-93-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

CARBON BLACK (1333-86-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

ETHYLBENZENE (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHY N-PROPYL KETONE (107-87-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

MIBK (108-10-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

N-BUTYL ACETATE (123-86-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

CARBON BLACK (1333-86-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

ETHYLBENZENE (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	54 µg/day

MIBK (108-10-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	Yes	No	No	

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TITANIUM DIOXIDE (13463-67-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

VM&P NAPHTHA (8032-32-4)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

TALC (14807-96-6)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

METHYL ETHYL KETONE (78-93-3)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

CARBON BLACK (1333-86-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List

ETHYLBENZENE (100-41-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

METHY N-PROPYL KETONE (107-87-9)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

MIBK (108-10-1)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

N-BUTYL ACETATE (123-86-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

TITANIUM DIOXIDE (13463-67-7)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 06/02/2016

BARRIER III HS PRIMER GRAY

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

H225	Highly flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life

SDS US (GHS HazCom 2012)

RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.